

Material releases wall / ceiling

Heating foil E-ENERGY CARBON FLEECE

Caution: Install E-ENERGY CARBON according to the installation instructions. Only use plastic spatula to press in the heating foil. Avoid kinks and folds. After installing the heating foil, a complete covering layer (filler, plaster system, tile, etc.) of at least 2 mm must be applied. Use recommended products in accordance with the manufacturer's instructions and the generally recognised rules of technology. **TIP:** Check in the manufacturer's instructions when the heating system can be put into operation. In the case of tile coverings, this can take up to 28 days.

Covering / Top layer	Wall coverings, coatings and fillers
Embedding heating foil	Capacoll GK 250g or with Akkordspachtel SXL (top layer min. 2 mm) Sand dry filler and prime with CapaSol
Sealing in damp areas	–
Putty	Dispersion filler: StuccoDecor Di Luce, Stucco Satinato, Stucco Eleganza, Arte Twin Lime putty: Calcino Decor, Calcino Romantico Due to the brittleness of the lime materials, the embedding of Capaver G45SP in the last filler layer of the Akkordspachtel SXL recommended
Wall coverings	Capaver-Sortiment bonded with CapaColl GK or VK
Textured coating	MultiStruktur as top coat or as intermediate coating for glaze coatings
Glaze coating	DecoLasur Matt und Glänzend as well as ArteLasur and ArteLasur Color, Arte Velvet and Arte Dolce
multicolor coatings	System VarioChips, VarioFloc, VarioPutz and VarioStone